

Ortofon MC Samba and Salsa

TECHNICAL DATA	MC Samba	MC Salsa
Output voltage at 1000 Hz, 5cm/sec.	300 μ V	380 μ V
Channel balance at 1 kHz	< 1 dB	< 1 dB
Channel separation at 1 kHz	> 25 dB	> 25 dB
Channel separation at 15 kHz	> 15 dB	> 15 dB
Frequency range at - 3dB	20-30.000 Hz	20-35.000 Hz
Frequency response FIM distortion at recommended	20-20.000 Hz +/- 2 dB	20-20.000 Hz +/- 2 dB
Tracking force, DIN 45.542	< 1%	< 1%
Tracking ability at 315Hz at recommended tracking force	> 70 μ m	> 80 μ m
Compliance, dynamic, lateral	14 μ m/mN	15 μ m/mN
Stylus type	Nude elliptical	Super Fine Line
Stylus tip radius	r/R 8/18 μ m	r/R 5/40 μ m
Equivalent stylus tip mass	0,50 mg	0,40 mg
Tracking force range	1,3-1,8 g (13-18 mN)	2,0-2,4 g (20-24 mN)
Tracking force, recommended	1,5 g (15 mN)	2,2 g (22 mN)
Tracking angle	20°	20°
Internal impedance, DC resistance	6 Ohm	7 Ohm
Recommended load impedance	> 10 Ohm	> 20 Ohm
Cartridge body material	Noryl	Noryl
Cartridge colour	Yellow transparent	Orange transparent
Cartridge weight	7 g	7 g



Ortofon MC Samba



Ortofon MC Salsa

